


**NOTES:**

ALL APPLICABLE DETAILS AND NOTES FROM STANDARD PLAN 15 APPLY TO ALTERNATE SIDE SEWER INSTALLATIONS.  
 ALTERNATE SIDE SEWER INSTALLATION ALLOWED WITH PRIOR APPROVAL FROM THE DISTRICT AND ONLY WHEN STANDARD SIDE SEWER INSTALLATION PER STANDARD PLAN 15 AND 24 ARE NOT POSSIBLE BY:


- A. CUTTING THE SIDE SEWER STUB BACK TO ALLOW THE PIPE TO BE INSTALLED WITHIN THE DISTRICT REQUIRED SLOPES (100% MAX./ 2% MIN.) TO THE BUILDING CONNECTION.
- B. ROUTING THE SIDE SEWER PIPE TO EXTEND ALONG SIDE THE BUILDING TO DECREASE SLOPE.

IF THE ALTERNATE SIDE SEWER INSTALLATION IS ALLOWED, A PLAN AND PROFILE OF THE SIDE SEWER INSTALLATIONS WILL BE REQUIRED. PLAN AND PROFILE SHALL SHOW ALL UNDERGROUND UTILITIES WITH THE REQUIRED SEPARATIONS. SEE WWD GP-11 REQUIRED DRAWINGS-COMPOSITE UTILITY PLAN.



Woodinville  
Water District

ALTERNATE SIDE SEWER  
INSTALLATION



SEWER STD.  
PLAN NO. **15A**

REVISION DATE  
04/25