

6.5" OF  $\frac{5}{8}$ " CRUSHED GRAVEL (MIN.) REQUIRED IN HARD SURFACED AREAS. COMPACT TO 95% MAX. DENSITY. LOCAL JURISDICTIONAL REQUIREMENTS SHALL OVERRIDE.

SURFACE RESTORATION IN ACCORDANCE WITH LOCAL JURISDICTIONAL REQUIREMENTS. MINIMUM REQUIREMENTS SHOWN IN TRENCH PAVEMENT & SURFACE RESTORATION DETAIL NO. 8.

1  $\frac{1}{4}$ " CRUSHED BACK FILL. SEE NOTE 1.

SPECIAL PRECAUTIONS SHALL BE TAKEN TO PROTECT PIPE TO THIS LEVEL. SEE SPECIFICATIONS FOR MAXIMUM PARTICLE SIZE.

BEDDING GRAVEL

O.D. OF WATER MAIN

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

4"

</